



Aislamientos 2 | 2. PARA CUBIERTAS POLIEXPAN Y POLIEXFOAM

POLIESTIRENO EXPANDIDO	MEDIDAS (CM)	TIPO	€/UND
	100*200*2	I	2,39
	100*200*3	I	3,58
	100*200*4	I	4,79
	100*200*5	I	5,98



BOVEDILLAS DE EXTRUIDO	MEDIDAS (CM)	TIPO	€/UND
	100*62,5*15	I	5,61
	100*62,5*17	I	6,34
	100*62,5*20	I	7,48
	100*62,5*22	I	8,21
	100*62,5*25	I	9,34



POLIESTIRENO EXTRUIDO

A	PRODUCTOS Y CARACTERISTICAS	ESPESOR	M2 PAQUETE	M2 PALET	M2 CAMION	€/M2	
	Dimension: 1,25*0,60 Uso: Paredes con cámara, tabiquería seca	30	10,5	126	2.520	4,73	
		40	7,50	90	1.800	6,31	
		50	6,00	72	1.440	7,88	
		60	5,25	63	1.260	9,46	

C	PRODUCTOS Y CARACTERISTICAS	ESPESOR	M2 PAQUETE	M2 PALET	M2 CAMION	€/M2	
	Dimension: 1,25*0,60 Uso: Cubierta invertida	30	10,5	126	2.520	4,80	
		40	7,50	90	1.800	6,39	
		50	6,00	72	1.440	7,99	
		60	5,25	63	1.260	9,59	

T	PRODUCTOS Y CARACTERISTICAS	ESPESOR	M2 PAQUETE	M2 PALET	M2 CAMION	€/M2	
	Dimension: 1,25*0,60 Uso: Cubiertas inclinadas bajo teja (acanalada)	40	10,50	144	1.728	6,65	
		50	7,50	115,2	1.382	8,32	